



Scotch®

Super 88 Vinyl Electrical Tape

Data Sheet



Product Description

Scotch Super 88 Electrical Tape is a premium grade, 0.2mm thick, all-weather vinyl insulating tape. It is designed to perform continuously in a temperature ambient of -40°C to 105°C (220°F). The tape is conformable for cold weather application down to -18°C (0°F). It has excellent resistance to abrasion, moisture, alkalis, acids, corrosion and varying weather conditions (including ultraviolet exposure). The combination of elastic backing and aggressive adhesive provides moisture-tight electrical and mechanical protection with minimum bulk. Super 88 is an Underwriters' Laboratories Listed and Canadian Standards Association Certified "Insulating Tape".

Tape Features

- ❖ Polyvinyl chloride backing.
- ❖ Pressure sensitive rubber based adhesive.
- ❖ Thickness 0.216mm.
- ❖ Dielectric breakdown 10kV.
- ❖ Cold weather pliability and adhesion.
- ❖ Flame retardant.
- ❖ Excellent abrasion and puncture resistance.
- ❖ High tensile and mechanical strengths.
- ❖ Good elongation for excellent conformability to irregular surfaces.
- ❖ Resistant to weathering, salt water, alkalis and acids.
- ❖ Inhibits corrosion of electrical conductors.
- ❖ Consistent electrical strength when wet.
- ❖ Compatible with all standard cable insulations.
- ❖ Compatible with epoxy and polyurethane resins.
- ❖ Meets BS 3924.
- ❖ UL Listed, UL 510 standard 'insulating tape' (product category OANZ) file E129200.
- ❖ CSA certification, standard C22.2 No. 197-M1983 'PVC insulating tape', file LR48769.

Applications

- ❖ Primary electrical insulation for all wire and cable splices rated up to 600 volts and 105°C.
- ❖ Forms a protective abrasion resistant cover for high voltage cable joints and terminations.
- ❖ For fixed wire joints up to 1000V.
- ❖ For harnessing wires and cables.

Data – Physical and Electrical Properties

Physical Properties

Test Method	Typical Value*
-------------	----------------

Temperature Rating:

UL 510	80°C (176°F)
--------	--------------

CSA C22.2 No.197-M1983	
------------------------	--

Handling	-18°C (0°F)
----------	-------------

Continuous Operation	105°C (220°F)
----------------------	---------------

Colour	Black
--------	-------

Thickness ASTM-D1000	0.2mm
----------------------	-------

Adhesion to Steel ASTM-D1000

22°C (72°F)	2.75N/cm
-------------	----------

-18°C (0°F)	6.6N/cm
-------------	---------

Adhesion to Backing ASTM-D1000

22°C (72°F)	2.75N/cm
-------------	----------

-18°C (0°F)	6.6N/cm
-------------	---------

Breaking Strength ASTM-D1000

22°C (72°F)	35.5N/cm
-------------	----------

Ultimate Elongation ASTM-D1000

22°C (72°F)	250%
-------------	------

-18°C (0°F)	100%
-------------	------

Flammability (Maximum)

UL 510	1 sec.
--------	--------

ASTM-D1000	4 sec.
------------	--------

Accelerated Ageing

ASTM-D1000	80%
------------	-----

Flagging ASTM-D1000	<25mm
---------------------	-------

Telescoping

24 Hours @ 50°C (120°F)	<25mm
-------------------------	-------

Electrical Properties

Test Method	Typical Value*
-------------	----------------

Voltage Rating U1510	600V
----------------------	------

Dielectric Breakdown ASTM-D1000	
---------------------------------	--

Standard Condition	10000 volts
--------------------	-------------

High Humidity	90% of std.
---------------	-------------

Insulation Resistance	
-----------------------	--

ASTM-D1000	>1 x 10 ⁶ megohms
------------	------------------------------

(High Humidity Method)	
------------------------	--

Note: These are typical values and should not be used for specification purposes.

WOKING

Unit 19, Woking Business Park, Albert Drive,
Woking GU21 5JY
Tel: 01483 747747 • Fax: 01483 747001

BRISTOL

The Alpha Centre, Armstrong Way, , Great Western
Business Park, Yate, Bristol BS37 5NG
Tel: 01454 322555 • Fax: 01454 323555

NORTON CANES

Unit 15-16, Bellsizes Close, Norton Canes,
Staffordshire WS11 9TQ
Tel: 01543 450555 • Fax: 01543 450600

**Scotch®**

Super 88 Vinyl Electrical Tape

Data Sheet

Product

The tape is based on polyvinyl chloride (PVC) and/or its copolymers and has a rubber-based, pressure-sensitive adhesive. The tape shall be 8.5 mils thick, and be UL Listed and marked per UL Standard 510 as “Flame Retardant, Cold and Weather Resistant”. The tape must be applicable at temperatures ranging from -18°C through 38°C (0°F through 100°F) without loss of physical properties. The tape shall be classified for use in both indoor and outdoor environments. The tape shall be compatible with synthetic cable insulations, jackets and splicing compounds. The tape will remain stable and will not telescope more than 0.1 inches when maintained at temperatures below 50°C (120°F).

Engineering/Architectural Specification

Primary electrical insulation (branch wiring in wet or dry locations): All splices for 600 volt wire rated 105°C (220°F) and below shall be insulated with a minimum of two half-lapped layers of Scotch Super 88 Vinyl Electrical Tape. All connectors having irregular surfaces shall be padded with Scotchfil Electrical Insulation Putty or Scotch 130C Rubber Splicing Tape prior to insulating with Scotch Super 88 Tape. Mechanical protection (outer jacketing): All rubber and thermoplastic insulating high voltage power cable tape splices and repairs shall be over-wrapped with at least two half-lapped layers of Scotch Super 88 Vinyl Electrical Tape.

Installation Techniques

The tape shall be applied in half-lapped layers with sufficient tension to produce a uniform wind (for most applications this tension will reduce the tape’s width to approximately 5/8 of its original width). On pigtail splices, the tape shall be wrapped beyond the end of the wires and then folded back, leaving a protective cushion to resist cut-through. Wrap tape up-hill, taping from a small diameter surface to a larger diameter surface. Apply the tape with no tension on the last wrap to prevent flagging.

Maintenance

Scotch Super 88 Tape complies with the requirements of UL 510 for storage. When maintained under normal storage conditions the tape will remain stable and has a five-year shelf life.

Important Notice

Technical information provided by 3M is based on experience and/or tests believed to be reliable, but their accuracy is not guaranteed and the results may not be relevant to every user’s application. For this reason 3M does not accept responsibility or liability, direct or consequential, arising from reliance upon any information provided and the user should determine the suitability of the products for their intended use. Nothing in this statement will be deemed to exclude or restrict 3M’s liability for death or personal injury arising from its negligence. All questions of liability relating to 3M products are governed by the seller’s terms of sale subject where applicable to the prevailing law. If any goods supplied or processed by or on behalf of 3M prove on inspection to be defective in material or workmanship, 3M will (at its option) replace the same or refund to the Buyer the price paid for the goods or services. Except as set out above, all warranties and conditions, whether express or implied, statutory or otherwise are excluded to the fullest extent permissible at law.

3M and Scotch are trademarks of the 3M Company. Printed in the UK.
© 3M United Kingdom PLC, Issue 2,,04/11

WOKING

Unit 19, Woking Business Park, Albert Drive,
Woking GU21 5JY
Tel: 01483 747747 • Fax: 01483 747001

BRISTOL

The Alpha Centre, Armstrong Way,, Great Western
Business Park, Yate, Bristol BS37 5NG
Tel: 01454 322555 • Fax: 01454 323555

NORTON CANES

Unit 15-16, Bellsizes Close, Norton Canes,
Staffordshire WS11 9TQ
Tel: 01543 450555 • Fax: 01543 450600